

# Product Bulletin

## Concept® 203-OAP FLEXIBLE GLOSS WHITE PVC PERMANENT ADHESIVE

Concept® 203-OAP is a 3-mil premium white gloss flexible calendared vinyl film coated with 200-5031 permanent gray acrylic pressure sensitive adhesive laminated to a 90# layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems. Adhesive 200-5031 offers good opacity with low initial tack building to a permanent bond within 24 hours providing repositionability to the graphic during application. The 90# liner offers excellent product layflat in a variety of ambient conditions.

<b>Applications</b>	Concept® 203-OAP is designed for interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays.	
<b>Thickness</b>	Film	3.0 mils.
	Adhesive	.8 to 1.0 mils.
	Liner	6.7 mils.
	(Thickness variance +/- 10%)	
<b>Dimensional Stability</b>	Good.	
<b>Temperature Ranges</b>	Minimum application temperature	+40°F.
	Service temperature	-40°F to +180°F.
<b>Expected Exterior Exposure</b>	Up to 5 years.	
<b>Adhesion</b>	To stainless steel	40 oz/in.
	PSTC-101 Method A with 24 hr. dwell at 70°F and 50% relative humidity.	
	Typical values. Individual values may vary.	
	Test thoroughly for your specific application.	
<b>Water Resistance</b>	Good. Test if immersed.	
<b>Humidity Resistance</b>	Good.	
<b>Solvent Resistance</b>	Good	
<b>Storage Stability</b>	6-month shelf life when stored at 70°F and 50% relative humidity.	
<b>Product Codes</b>	203-OAP-30	(30" x 150' roll)
	203-OAP-54	(54" x 150' roll)
	203-OAP-54RW	(54" x 150' roll, reverse wound/ notched core)
	203-OAP-60	(60" x 150' roll)
<b>Recommendations</b>	Completely evaporate ink solvents before application. Failure to do so may facilitate solvent penetration resulting in premature vinyl degradation.	



**Manufacturer of Pressure Sensitive Films,  
Traffic Graffiti Floor Advertising Films,  
Custom Coatings and Printing Inks.**

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537  
Web Site: [www.generalformulations.com](http://www.generalformulations.com) • e-mail: [gfiinfo@generalformulations.com](mailto:gfiinfo@generalformulations.com)

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.