

PSG® SupraLAM Overlaminates

Product Description

PSG® SupraLAM family of products are intended for use on printed substrates that are applied to indoor and outdoor surfaces to enhance overall graphic depth while protecting printed materials from UV radiation, environmental elements and general abuse.

Technical Data

Face Material	3 mil Gloss/Matte/Luster Flexible Vinyl
Adhesive	Clear Pressure Sensitive Permanent Acrylic
Liner	53# Paper
Opacity	Clear
Outdoor Durability	Up to 5 Years

Applications

Flat and Simple Curves Only
Auto/Bus Markings
Indoor Graphics
Outdoor Signage

Typical Characteristics

Adhesion	1 ± 0.2 mil
Minimum Application Temperature	35°F
Service Temperature Range	-20°F to +150°F
Shelf Life (@ 70°F, 50% RH)	1 Year
Water Resistance	Good
UV Resistance	Up to 5 Years
Solvent Resistance	Good for most petroleum solvents and lower aliphatic alcohols. For maximum solvent resistance, edge sealing is recommended.

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)