

# PSG<sup>®</sup> SupraMOUNT Calendered

## Product Description

SupraMOUNT calendered films are intended for use as an overlaminating film on printed substrates that are applied to indoor and outdoor surfaces such as bus or automobile markings, buildings; signage; etc. SupraMOUNT Overlaminates are excellent at enhancing overall graphic depth while protecting printed materials from UV radiation, environmental elements, and general abuse.

## Technical Data

Face Material	3 mil Clear/Matte/Luster Calendered Vinyl
Adhesive	Permanent / Permanent Clear Acrylic
Liner	53# Paper
Opacity	Clear
Outdoor Durability	Up to 5 Years

## Applications

Decals  
Fleet and Bus Graphics  
Building Graphics

## Typical Characteristics

Adhesion (Permanent)	1 ± 0.2 mil
Minimum Application Temperature	35°F
Service Temperature Range	-20°F to +150°F
Shelf Life (@ 70°F, 50% RH)	1 Year
Water Resistance	Good
Humidity Resistance	Good
Solvent Resistance	Good for most petroleum based solvents. Ultimate resistance to solvents is highly dependent on the substrate used. Edge sealing is recommended in high solvent exposure areas

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)