

Makrofol® SR906 1-1 040009

Description and Application Information

Makrofol® SR906 1-1 040009 is a clear transparent extruded polycarbonate film with an acrylic functional layer. The film comprises a high UV protection additive. The acrylic on the top surface offers improving scratch resistance while the polycarbonate back surface provides excellent printability.

The combination of the acrylic functional layer and the polycarbonate layer of Makrofol® SR906 040009 overcomes the low impact resistance of PMMA films. The UV protection benefits a low change in the yellowness index even if passing the weathering test. Additionally, Makrofol® SR906 1-1 040009 film has good heat resistance and excellent impact strength.

Makrofol® SR906 1-1 040009 is especially designed for the Film Insert Moulding (FIM) process. Excellent formability by High Pressure Forming (HPF) as well as thermal forming processes are possible. Due to the acrylic functional layer Makrofol® SR906 040009 can be used as well for injection overmolding with Acrylic or backmolding with Polycarbonat giving high film/resin adhesion even passing typical climate test conditions for automotive interior parts.

Makrofol® SR906 1-1 040009 has been designed for applications in the automotive interior, IT and EE sector. It is available in the standard thickness range of 175, 250, 375 and 635 µm. Surface structure is gloss-gloss.

Makrofol® SR906 040009 is supplied with the protective masking film on both sides.

Guide data*

General properties			
Property	Value	Unit of measurement	Method
Density	1.2	g/cm ³	ISO 1183, 20°C, Method C
Gloss			ISO 2813, Angle 60°, backprinted black
1 - surface	≥ 85	digits	
Roughness R3z			following ISO 4287/88
1 - surface	≤ 0.5	µm	
Pencil hardness	≥ F		ASTM D 3363, 750g
Taber abrasion			ASTM D 1044, ASTM D 1003
Haze after 500 cycles	< 20	%	

Makrofol® SR906 1-1 040009

Optical properties			
Property	Value	Unit of measurement	Method
Light transmission	≥ 89	%	acc. to ISO 13468-2
Yellowness index	< 1		ASTM D1003
Haze			ASTM D 1003
1 - surface	≤ 0.5		
UV resistance			acc. to DIN ISO 4892-A D 65/10°
(YI after weathering test, 1000 hours) 1.1			
Mechanical properties			
Property	Value	Unit of measurement	Method
Stress at break	> 50	MPa	ISO 527-1,3 23°C
Strain at break	> 5	%	ISO 527-1,3 23°C
Tensile modulus	> 2200	MPa	ISO 527-1,3 23°C

* These values provide general information and are not part of the product specification.

Labeling and REACH applications

This product data sheet is only valid in conjunction with the latest edition of the corresponding Safety Data Sheet.

Any updating of safety-relevant information – in accordance with statutory requirements – will only be reflected in the Safety Data Sheet, copies of which will be revised and distributed. Information relating to the current classification and labeling, applications and processing methods and further data relevant to safety can be found in the currently valid Safety Data Sheet.



Makrofol[®] SR906 1-1 040009

The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations, are beyond our control. Therefore, it is imperative that you test our products, technical assistance, information and recommendations to determine to your own satisfaction whether our products, technical assistance and information are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by Covestro. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale which are available upon request. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with any claim of any patent relative to any material or its use. No license is implied or in fact granted under the claims of any patent.

This product is not designated for the manufacture of a medical device (1) or of intermediate products for medical devices. This product is also not designated for Food Contact (2), including drinking water, or cosmetic applications. If the intended use of the product is for the manufacture of a medical device or of intermediate products for medical devices, for Food Contact products or cosmetic applications Covestro must be contacted in advance to provide its agreement to sell such product for such purpose. Nonetheless, any determination as to whether a product is appropriate for use in a medical device or intermediate products for medical devices, for Food Contact products or cosmetic applications must be made solely by the purchaser of the product without relying upon any representations by Covestro.

(1) Please see the "Guidance on Use of Covestro Products in a Medical Application" document.

(2) As defined in Commission Regulation (EU) 1935/2004.

Editor: Covestro (Hong Kong) Limited
Covestro AG
43/F, Hopewell Center, 183 Queen's Road East
Wanchai, Hong Kong

Distributed by:



Piedmont Plastics[®]

where solutions take shape

Toll Free: 1.800.277.7898

www.piedmontplastics.com