



MATERIAL SPECIFICATIONS

- MATERIAL:** White foil-based media + photoluminescent / texture + PSA + release liner = <20 mil.
- SIZE:** Standard rolls: 26.5" wide x 10' long and 26.5" wide x 30' long.
- PRINT COMPATIBILITY:** Solvent, eco-solvent, latex, and UV wide format digital printers.
- OVERLAMINATE:** No overlaminate needed. Print direct to the surface / one step production process.
- ADHESIVE:** Pressure sensitive, permanent acrylic; typically no residue when removed.
- LINER:** 84# silicone based stay flat release liner.
- APPLICATION:** No heat source and dry apply; does not require professional installers. Roller recommended to compress to surface.
- USAGE:** Indoor floor & wall surfaces (textured & non-textured) including cinder block, brick, concrete (sealed & unsealed), tile, terrazzo and vinyl flooring.
- LIFE EXPECTANCY:** Printed and installed up to 1 year with pedestrian traffic.
- NOTES:**
1. Handle rolls with care, do not drop on end. Store horizontal with suspension caps.
 2. Use a take up roll with tension and vacuum to keep material flat during printing.
 3. Print direct to the surface; download profiles from AlumiGraphics.com.
 4. Cut-to-shape on most print & cut, plotters and routers, guillotine, steel rule die cut and manually with scissors. Use 60° or carbine tip blades on AlumiGraphics Grip.
 5. Material is pliable, lightweight, has no memory and will not shrink.
 6. Withstands high temperature range; -40° F - 302° F / -40° C - 150° C.
 7. Premium grade photoluminescent surface. Charges from any light source, glows when lights go out. Reveal areas glow bright, printed areas less.
Contact FloorSignage regarding use for safety compliance.
 8. Meets slip resistant standards, dry & wet: ANSI A137.1, UL 410, ASTM D2240-05, HB198:2014, British BS 7976-2/UKSRG, Australian AS 4586:2013 (app. D) =R11.
 9. Meets surface burning ASTM E84-15b (NFPA 255, ANSI/UL 723, UBC 8-1).
 10. Environmentally friendly, contains no PVC; dispose with aluminum recycling.
 11. Harmonized tariff code / NCM: 7607.20.0000.
 12. Shelf Life = 2 years stored at 70° F / 21° C.

DESIGNED FOR END USERS TO INSTALL & REMOVE

STANDARD APPLICATION INSTRUCTIONS

1. Always use hard rubber roller rather than a squeegee.
2. Recommended surface temperate 50° Fahrenheit / 10° Celsius or higher.
3. Sweep dry surface clean of dirt & debris.
4. Lay printed side down on a flat surface then peel release liner from the foil surface.
5. Lay adhesive side down flat on the selected location.
6. Smooth by hand from the center to outer edge, be sure all edges lay flat.
7. Firmly compress to surface, especially all edges by roller.

REMOVAL INSTRUCTIONS

1. Generally easy to remove on wall and pedestrian walkway applications; rough surfaces and/or vehicular traffic may increase the difficulty in removal.
2. Simply peel off at an angle less than 45 degrees for best result; typically leaves no residue.

Manufactured in the United States by

FLOOR SIGNAGE, LLC

PIONEERING DIGITAL PRINT MEDIA FROM THE GROUND UP!

