

Product Bulletin

Concept[®] 210 TRAFFIC GRAFFIC[®] BASE VINYL REMOVABLE ADHESIVE

Concept[®] 210 is a specially formulated flexible vinyl with a high performance acrylic pressure sensitive adhesive on a 90# stay-flat liner. The combination of vinyl and adhesive allows removability of the film from most common commercial tile floor substrates for up to 6 months under normal exposure conditions. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems.

Applications	Concept [®] 210 is designed for temporary floor signs, decals, and point of purchase advertising. Must use either Concept [®] 109 or Concept [®] 211 (overlaminated) to provide protection to the graphics.	
Thickness	Film	3.4 mils.
	Adhesive	0.8 to 1.0 mils.
	Liner	6.7 mils.
	(Thickness variance +/- 10%)	
Temperature Ranges	Minimum application temperature	+40° F.
	Service Temperature	-40° F to +180° F.
Adhesion	To stainless steel	8 oz/in.
	PSTC-1 with 24 hour dwell at 70 F and 50 % relative humidity. Typical values. Individual values may vary. Test thoroughly before production.	
Removability	Up to 6 months from most common commercial tile floors. Floor must be clean before application. All tiles must be firmly attached to the sub floor. Painted floors must have excellent adhesion to the sub floor. Test all painted cement floors for adhesion of the paint before applying a floor decal.	
Water Resistance	Good. Do not saturate	
Humidity Resistance	Excellent.	
Solvent Resistance	Excellent.	
Storage Stability	6-months when stored at 70° F and 50% relative humidity.	
Product Code	210-54	(54" X 150' roll)
Recommendations	Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.	



**Manufacturer of Pressure Sensitive Films,
Traffic Graffice Floor Advertising Films,
Custom Coatings and Printing Inks.**

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions of Sale, Including Disclaimer of Warranties and Limitation of Liability.