

Product Bulletin

Concept[®] 250

Wall-Frog[™] Pressure Sensitive Fabric

Concept[®] 250 is a 4.0 mil matte white polyester fabric with an acrylic removable pressure sensitive adhesive backed by a 90# sta flat liner. Concept[®] 250 is formulated and manufactured to be chlorine and phthalate free*. The combination of fabric and adhesive allows removability of this product from normal wall surfaces. The 90# release liner provides excellent stability for processing using standard solvent, eco-solvent, UV curable and latex digital inks common to wide format digital printing systems.

Applications Concept[®] 250 is designed for temporary application of decals and graphics to most types of painted interior walls. This includes most flat, semi gloss and gloss paint finishes. Decals may also be applied to sealed wall coverings. The surface must be smooth and clean prior to application. Consult with paint manufacturer for correct paint cure time before applying Concept[®] 250 to freshly painted surfaces.

Thickness

Fabric	4.0 mils.
Adhesive	33.5 G/m ²
Liner	6.7 mils.
(Thickness variation +/- 10%)	

Dimensional Stability Good.

Temperature Ranges

Minimum application temperature	+40°F.
Service temperature	-40°F to +200 F.

Removability Removable up to 6 months under normal interior exposure conditions and applications. Removal of wall fabric should be done at a 180° angle while pulling slowly against itself.

Adhesion To standard test panels 4 to 12 oz. /in.
Tested according to PSTC-101 Method A procedures with 24 hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Bond to wall surfaces may vary. Test thoroughly before production.

Storage Stability 6 months shelf life when stored at 70°F and 50% relative humidity.

Product Code

Concept [®] 250-54	54" x 100'
Concept [®] 250-60	60" x 100'

* Chlorine and phthalates are not intentionally added to the formulation of Concept[®] 250. There is a possibility of trace contamination during raw material manufacturing.

Recommendations Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in product failure.



**Manufacturer of Pressure Sensitive Films,
Traffic Graffice Floor Advertising Films,
Custom Coatings and Printing Inks.**

309 S. Union • P.O. Box 158 • Sparta, Michigan 49345 • (616) 887-7387 • (800)253-3664 • FAX (616)887-0537
Web Site: www.generalformulations.com • e-mail: gfiinfo@generalformulations.com

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to General Formulations, Inc's Price List for Terms and Conditions or Sale, Including Disclaimer of Warranties and Limitation of Liability.