



# Paige

## SIGNWIRE

## spec

988182M 1000 ft.  
988182L 500 ft.

# Rip Strip<sup>TM</sup><sub>2</sub>



**LED CABLE**  
**18-2 CONDUCTOR**  
**UL LISTED**



Application: This cable consists of 2 conductor 18 AWG stranded tinned copper conductor with a Polyvinyl Chloride jacket overall. UL Listed for sunlight resistant applications. RoHs II/REACH Compliant. Made in the USA.

### 1.0 CONSTRUCTION


#### 1.1 Conductor:

- 1.1.1 Material: Tinned Copper
- 1.1.2 Size: 18 AWG
- 1.1.3 Stranding: 7 Strands

#### 1.2 Lay Length:

- 1.2.1 This is a Zip-cord cable

#### 1.3 Jacket:

- 1.3.1 Material:  
Sunlight Resistant  
Polyvinyl Chloride
- 1.3.2 Wall Thickness: .025"
- 1.3.3 O.D.: .096" x .212"
- 1.3.4 Marking: "PAIGE RIP STRIP<sup>TM</sup> 2  
P/N (\*SEE BELOW) CONDUIT  
NOT REQUIRED E191597 (UL)  
CL2 18AWG 2C 105C SUN-RES  
OR  AWM I A/B 105°C 600V FT1  
FT2 OR LV LED WIRE 600V 105C  
LED6-18 ROHS II REACH  
MOISTURE RESISTANT MADE IN  
USA WWW.PAIGEELECTRIC.COM"  
(sequential footage markers)  
\*988182M – 1,000 ft. reel  
988182L – 500 ft. box

1.3.5 Color: Light Blue + Light Blue/Red

#### 1.4 Temperature / Voltage:

- 1.4.1 105°C / 600V

#### 1.5 Packaging:

- 1.5.1 P/N 988182M – 1000 ft. reel
- 1.5.2 P/N 988182L – 500 ft. box



Distributed by:

 **Piedmont Plastics<sup>®</sup>**

where solutions take shape

www.piedmontplastics.com

800.277.7898