

SupraMOUNT™

Make your message stick!

PSG® SupraMOUNT™ is a family of mounting films available in white, clear and optically clear options to deliver smooth distortion-free mounting for numerous applications. SupraMOUNT™ films are coated on both sides with a pressure sensitive acrylic adhesive designed for mounting photographic and digital prints to a variety of substrates. SupraMOUNT™ films are ideal for use with photographic, ink jet, electrostatic, lithographic and screen printed images.



Typical Applications

Clear & Optically Clear

- Recommended for mounting or face mounting of graphics onto glass, acrylic and other non-porous surfaces.
- SupraMOUNT™ Clear can be used for nameplates, backlit and POP displays, promo graphics and shop fronts.
- SupraMOUNT™ Optically Clear can be used for lenticular imaging applications, touchscreen displays and high quality photographic images.

White

- Great for image decal and high-volume mounting of graphics onto difficult substrates such as MDF, Gatorboard™, Ultraboard™, Foamex™ or Sintra™.
- Can be used for point of purchase displays, promotional products and temporary graphics.

Product Features

Clear & Optically Clear

- High tack, strong bond adhesive.
- Optically clear is made using the finest optical clarity components.
- Can be used on media printed with all common print technologies (Solvent, Eco-Solvent, Latex and UV).

White

- Excellent opacity provides ability to mount to dark substrates or mounting over old graphics allowing for the reuse of mounting substrates.
- Can be used on media printed with all common print technologies (Solvent, Eco-Solvent, Latex and UV).

Physical Characteristics

	Clear & Optically Clear	White
Film Thickness	1 mil	2 mil
Adhesive Layer	1 mil (on each side of film)	1 mil (on each side of film)
Outdoor Durability	Not recommended for outdoor use	Not recommended for outdoor use
Heat Resistance Range	-40° - 100° C (-40° - 212° F)	-40° - 100° C (-40° - 212° F)
Peel Strength (24 Hr Test)	4.1 PSI	4.1 PSI

Additional Notes

- Apply with roller laminator between room temperature and 49° C (120° F) at a speed between .3 - 2.5m (1-8 ft) per minute.
- A press is not recommended for applying PSG® SupraMOUNT™ Mounting Films.

Piedmont Sign Grade (PSG®) is a family of products designed for the sign industry that includes SupraFLEX® Banner, AluPOLY® ACM and a complete line of vinyls and laminates. Contact your local branch today for material pricing and availability.

Important: It is the user's responsibility to ensure the suitability and safety of the product for all intended uses. As a distributor, Piedmont Plastics does not warrant the merchantability of the product or the capability of the product for the purpose intended by the user. Users should independently test each material, prior to use, for suitability for their specific purpose according to instructions in any technical data sheet. Piedmont Plastics does not assume any responsibility or liability for any advice provided, or for performance or results of any installation or use of the product or any final product into which the product may be incorporated by the purchaser and/or user.

