

Universal LED Backlit Frame



Designed to be sleek and non obtrusive, our universal LED backlit frame offers even, consistent, bright and impactful illumination. A great advertising tool boosting visibility of any product! The thin profile and ease of use makes interchanging graphics a snap with no tools. Just flip open the front of the frame and insert graphics. As seen in airports, malls, retail stores, stadiums and restaurants. Custom frame colors available.

- Frame hangs vertically or horizontally.
- Hardware included for mounting on a wall or from a ceiling.
- For use with translucent graphics.
- Graphics can be easily changed by opening the front of the frame.
- Clear acetate cover included that protects translucent poster.
- Durable anodized aluminum frame construction.
- Thin profile extends .625" from wall surface.
- Excellent 3 Chip LED bulb technology delivers even, bright illumination.
- LED Life Expectancy: 50,000 hours when used continuously.
- Low energy usage. Input range 110 - 240V with 12V output.
- 8ft Output cord length
- Includes an On/Off switch on the output cord.
- Includes a 24" daisy chain to connect up to three frames with one plug.
- All power supplies are UL Certified.



Horizontal



Vertical

Available Sizes

- 8.5" x 11"
- 11" x 17"
- 17" x 22"
- 18" x 24"
- 22" x 28"
- 24" x 36"



where solutions take shape
www.piedmontplastics.com

Contact us today!
800.277.7898 Toll Free | 704.597.8200

Universal Frameless LED Backlit Frame



Our universal frameless LED backlit frame can either be hung from a ceiling or on a wall providing adaptability for multiple environments. Designed for a clean and modern look, the thin profile and ease of use makes interchanging graphics easy by simply unscrewing the standoffs and lifting the acrylic face from the frame.

- Frame hangs vertically or horizontally.
- For use with translucent graphics.
- Clear acrylic face that protects translucent graphic.
- Excellent 3 Chip LED bulb technology delivers even, bright illumination.
- LED Life Expectancy: 50,000 hours when used continuously.
- Low energy usage. Input range 110 - 240V with 12V output.
- 8ft Output cord length.
- Includes an On/Off switch on the output cord.
- All power supplies are UL Certified.

Available Sizes

- 8.5" x 11"
- 11" x 17"
- 17" x 22"
- 18" x 24"
- 22" x 28"
- 24" x 36"



Piedmont Plastics[®]

where solutions take shape
www.piedmontplastics.com

Contact us today!

800.277.7898 Toll Free | 704.597.8200

PP_7.17