

Royalite™ R60 Fire-rated sheet

Product Description

Royalite™ R60 is a rigid, fire-rated, proprietary thermoplastic sheet specifically formulated to meet the requirements of the FAR 25.853a flammability test. It provides outstanding color, gloss and grain control while virtually eliminating grain and gloss retention problems after forming that are often found in other fire-rated materials.

Royalite R60 combines very high impact strength and stiffness with excellent formability in deep draws. It has high resistance to normal food and environmental stains, making the material easy to clean.

Value Solution

Royalite R60 sheet's outstanding thermoforming abilities create sharp, crisply detailed parts even after thermoforming. Its advanced formulation allows it to retain its color and grain detailing long after it is thermoformed, making durable, great looking parts. In addition to its excellent thermoforming abilities, R60 offers very high impact strength. This reduces overall costs resulting from high part stiffness in down gauging.

Key Characteristics

The primary features and benefits of Royalite R60 fire-rated sheet are:

- High tensile strength
- Fire-rated - Passes FAR 25.853a flammability* test
- Excellent formability - Can be used for a variety of products of varied size and function
- High resistance to food and environmental stains - easily cleaned
- Very high impact strength - Durable, long-lasting parts
- Available in a wide range of colors and textures ranging from smooth to deep-textured



Markets and End-Use Applications

Aircraft

Currently, Royalite R60 is being used in aircraft interiors that must meet FAR 25.853a. Commonly used for small thermoformed parts such as tray tables, arm rests, etc.

Electronics/Appliances

It is also ideal for a wide range of applications, such as computers, electronic instrumentation and business machine housings where rigidity in thin gauges, good flammability rating, high impact strength and excellent color, gloss and grain control are required.



Distributed by:



Piedmont Plastics[®]

where solutions take shape

Toll Free: 1.800.277.7898

www.piedmontplastics.com

Copyright © 2013, PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.