

WeatherPro™ T-30 Performance-capped ABS Sheet

Product Description

WeatherPro™ T-30 is a uniquely-engineered, multi-layer thermoplastic composite, combining the appearance, chemical and weather resistance of specially formulated acrylic resins with the stiffness, impact strength and thermoforming characteristics of ABS. This provides customers with a tough, durable part that is also aesthetically pleasing.

Value Solution

WeatherPro T-30's engineered composition makes it an ideal choice for large part thermoforming. Its stiffness and high impact strength create tough, long-lasting parts for a variety of outdoor vehicular applications. Its excellent depth-of-image means that WeatherPro T30 looks great as well. WeatherPro T-30 makes for an excellent replacement for traditionally painted or gel-coated pieces.

Key Characteristics

The primary features and benefits of WeatherPro T-30 sheet are:

- Excellent depth of image - Creates aesthetically-pleasing parts that can replace painted or gel-coated parts
- High impact strength - Creates tough, durable parts capable of handling the demands of exterior vehicular applications
- Thermoformability - Formulated specifically with large part thermoforming in mind
- Intense color rendition - Available in vibrant, custom colors and metallics
- Superior surface hardness - Parts are scratch- and mar-resistant



Markets and End-Use Applications

Recreational Vehicles

Fenders, generator doors, light housings, and ground effects

Marine and Boating

Kayak and paddle boat decks and instrument panels

Building and Construction

Engine covers, fenders, and canopies

Leisure Vehicles

ATV, power sport, and utility vehicle applications

Agricultural Equipment

Fenders, roofing, and other exterior parts

Lawn and Garden

Fenders, front hoods, instrument fronts and canopies



Distributed by:



Piedmont Plastics[®]

where solutions take shape

Toll Free: 1.800.277.7898

www.piedmontplastics.com

Copyright © 2013, PolyOne Corporation. PolyOne makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. PolyOne makes no warranties or guarantees respecting suitability of either PolyOne's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. POLYONE MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.