

# dreamScape

## Product Packaging

Each roll is meticulously packaged in a re-usable suspension box or ultra sturdy tube.  
**( No flat spots, no creases, no splices )**

**STD Lengths:** 75', 150', 300'

**STD Widths:** 30", 48", 54", 60", 75"  
 (+/- 1/8")

**Core Diameter:** 3 inches i.d. Heavy-Duty

\*Custom lengths and widths available on request

## Physical Properties

**Product Weight:** 200z. per lineal yd., ( 130z. per sq. yd. )

**Vinyl Weight:** 170z. per lineal yd.

**Fabric Weight:** 30z. per lineal yd.

**Thickness:** 0.015 to 0.030 in.

\*depending on texture

**Fabric:** Poly-Cotton Osnaburg or Polyester Nonwoven

\*depending on texture

## Breaking Strengths, lbs. force

**Machine Direction-warp:**

\*Exceeds Type II minimum of 50lbs.

**Cross Machine Direction-fill:**

\*Exceeds Type II minimum of 55lbs.

## Tearing Strength, Scale

**Machine Direction-warp:**

\*Exceeds Type II minimum of 25lbs.

**Cross Machine Direction-fill:**

\*Exceeds Type II minimum of 25lbs

## Cold Crack Resistance @ 20 degrees F

No Change

## Heat Aging ( 7 days at 158 degrees F )

\*Does not become stiff, brittle, discolored, or show loss of grain

## Specifications/ Testing/ Certification

**Federal Specification:**

\*CCC-408-D,C,B,A \*Type II \*Class A

**CFFA Specification:**

\*CFFA-W-101-D \*Type II \*Class A

## Fire Testing

**ASTM-E84 Tunnel Test** Class A

**NFPA286 Corner Burn Test** Class A

**NFPA265 Corner Burn Test** Class A

**BS476 Part 6&7**

\*Meets or exceeds requirements for flame spread, smoke developments and flashover.

## Mold/Mildew/ Bacterial Resistance

**ASTM-G21 Specifications:** Passed all requirements of CCCW-408-D

## Environment

**NYC MEA:** Register

\*Cadmium and Lead Free Formulation



dream it...print it...hang it...  
 dream it...print it...hang it...

Distributed by:



**Piedmont Plastics**

where solutions take shape

Toll Free: 1.800.277.7898

www.piedmontplastics.com