

Product Description:

FreePost® Wall Lizard™ is a removable, bubble-free, environmental friendly high quality printing media with SCITOP's patented gecko's toe pad cling technology. It is ideal for short term and long term indoor and outdoor application, such as seasonal retail sales, trade show, office poster, signage, etc.

FreePost® Wall Lizard™ can be easily applied to most clean and smooth surfaces. It leaves absolutely no residue when removed, even after long application period.

Cautions:

- Not recommended for outdoor usage.
- To optimize print results, printer needs to be set for highest print quality.
- Avoid hand oil and dirt contaminate the dot surface.
- Keep the film flat during application, crease and curing will affect the adhesion persistence.
- Due to different applying surface and environment, we can not guarantee the material will work on every condition. Please always test on applying surface before large scale usage.

General Information:

- 140µm (0.0055") Semi Clear PET film
- ECO-solvent, UV Digital, Latex printing compatible
- Semi Clear surface
- One side self-adhesive with liner

Storage:

- Store at temperature conditions of 10~25°C (50~77°F) and 50% relative humidity.
- We recommended that you always keep this product in its original packaging.

Feature:

- Gecko's toe pad design.
- Non-static, non-traditional adhesive design.
- Bubble-free, easy and quick to install.
- No residue on application surface.
- Removable, repositionable and reusable.
- Can be applied to most smooth surface.

Installation and Handling:

- The application area should be clean and free of dirt.
- Using water to assist applying the material is not necessary and not recommended.

Advantage :

- Very easy and quick to install. Almost everyone can install this material by themselves easily. Skilled person is not required.
- Very easy and quick to remove. Skilled person is not required.
- No residual at all even in very long application period. No need to clean surface after removing the material.

Product Specification:

Film Thickness	140±9µm (0.0055"±0.00035 ")
Total Thickness	190±12 µm (0.0071"±0.0004 ")
Film Weight	175±11 gsm (5.15±0.30 oz/yd ²)
Total Weight	245±15 gsm (6.80±0.40 oz/yd ²)
180°Peel Strength	10~30g/25mm
Release force	10~30g/25mm
Elongation at Break	>80%
Appearance	Semi Clear
Working Temperature	-30°C to 130°C (-22°F to 266°F)
Dimensional Stability	≤0.1 in
Shelf Life	Two years

Benefit :

- Minimum or no installation cost.
- Time saving.
- No cleaning cost.

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. Therefore we can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. The user is responsible for determining whether the FreePost® product is fit for a particular purpose and suitable for the user's method of application.

Application:

- Indoor & outdoor application.
- Short term application such as seasonal retail sales, trade show.
- Long term application such as office poster, signage.
- Suitable for most clean and smooth surfaces such as: Glass, Metal, etc.

Print Compatibility :

ECO-solvent / UV Digital / Latex printing compatible

Distributed by: