

<b>Project</b>	<b>Type</b>
<b>Catalog #</b>	

## DESCRIPTION

US LED delivers the ultimate signage solution in our TD3 product. TD3 offers the same light consistency at an 18" depth as it does at a 3" depth, while also offering options for a 12V power supply and a 24V power supply. The most proficient signage product at maintaining light levels, while saving you money. With a 5-year warranty and options for both, single and double faced sign cabinets, there is no other option.



## FEATURES AND SPECIFICATIONS

- Module can run off 12VDC or 24VDC
- 155° beam angle
- Can be used in 3" to 18" cabinet depths
- IP66 rated for protection from dust and moisture
- Multiple mounting options for single and double faced signs
- 5-year warranty



## ORDERING INFORMATION

Example: TD3-3-UN-65

Series	LEDs per Module	Input Voltage	Color
TD3	3	UN 12V/24V	65 6500K

### POWER SUPPLY AND LOADING SPECS

	Min # of Modules	Max # of Modules	US LED Model Number
12V-60W Load	4	12	PSA-12-60 (LED120A0012V50F)
24V-100W Load	2	20	PSA-24-100 (LEDINTA0024V41F0)

### MODULE SPACING - Single and Double Faced

Distance from Face	18"	12"	10"	8"	6"	4"	3"
Spacing Row to Row	24"	24"	22"	20"	18"	12"	8"

### ENERGY DATA

Input Voltage (V DC)	12/24
Module Level Power (W/ft)	4.5
Delivered Lumens (Lm/ft)**	360
Viewing Angle (°)	155
Correlated Color Temp (K)	6500
CRI	80
Ingress Protection	IP66
Module Dimensions	9.621" x 0.870" x 0.3"

\*\*1 module with wires = 14"

\* US LED product 'Lifetimes' refer only to the LED light engine, not the power source, and are based on the Illuminating Engineering Society's TM21 Calculated Lumen Maintenance methodology at a 25°C/77°F ambient temperature. The lifetimes are solely meant to be a guide for expected LED degradation and not a warranty or predictive of their actual life, which can be affected by ambient temperatures and other factors



Distributed by:



Toll Free: 1.800.277.7898  
www.piedmontplastics.com