

Point4

Channel Letter Lighting | 3"-9" Channel Letter Depth

Project	Type
Catalog Number	

Rev #	1/10/18-1
-------	-----------

Description

The Point4 module brings simplicity to sign lighting with its patented and convenient Quick Connect tabs, and is offered in a variety of color temperatures. The Point4 is intended for depths of 3"-9", powered by 12VDC, and is the easiest and fastest system to install on the market.



The Point4™

Features

- Patented Quick Connect tabs - easiest and fastest system to install on the market
- No need for cutting or splicing wires
- Suitable for damp locations
- Class 2 compliant
- Can be used in 3"-9" channel letter depths
- 5-year warranty

Certifications

- UL Recognized (US and Canada)
- UL Classified (US and Canada) for retrofits

Specifications

Dimensions: 2.2" x .75" x .31"

Energy Data - 3 Modules / Foot

Input Voltage (V DC)	12
Module Level Power (W/Ft)	1.5
System Level Power (W/Ft)	1.75
Delivered Lumens (Lm/Ft)**	150
Efficacy (Lm/W)	100
Viewing Angle (°)	120°
Color Temperature (K)	6500
L70 Calculated Life (Hrs.)**	>200,000
Typical Stroke (in)****	6"
Operating Temperature (°C)	-40 to 60

Packaging Specs

Master Case:	810 Modules (270 Feet)
Inner Case:	270 Modules (90 Feet)
Tray:	90 Modules (30 Feet)

* System power consumption, which includes power supply losses

** Estimated light output under application operating conditions

*** US LED product 'Lifetimes' refer only to the LED light engine, not the power source, and are based on the Illuminating Engineering Society's TM21 Calculated Lumen Maintenance methodology at a 25°C/77°F ambient temperature. The lifetimes are solely meant to be a guide for expected LED degradation and not a warranty or predictive of their actual life, which can be affected by ambient temperatures and other factors.

**** For 5 inch deep can

Ordering Information

Series	Variant	Input Voltage	Color
PT4	3	12	W - 6500K White

Example: PT4-3-12-W

Power Supply Loading Specs

Series	Min # of Modules	Max # of Modules	Part Number
12W Load	12	22	PSA-12-12 (LED120A0012V10F)
60W Load	24	110	PSA-12-60 (LED120A0012V50F)
			PSA-12-60V (LED120A0012V50FO)

Distributed by:



Toll Free: 1.800.277.7898

www.piedmontplastics.com